MSX-765
L-/S-BAND T&C TRANSCEIVER

L3 has a rich heritage of flight-proven satellite products. High-reliability space communications equipment has been one of our primary business thrusts since 1968, beginning with the transmitters supplied for the Apollo program.





L3 Telemetry & RF Product (L3 T&RF) has a rich heritage of flight-proven satellite products. High-reliability space communications equipment has been one of our primary business thrusts since 1968, beginning with the transmitters supplied for the Apollo program.

The MSX-765 is designed to meet the next-generation needs for command reception and telemetry transmission for U.S. Department of Defense (U.S. DoD), NASA and commercial high-reliability satellite applications where mass is critical and higher uplink command rates are required.

The MSX-765 is a DSP-based design using technologies developed for the CXS-2000 multi-mode, multi-band transponder. The unit consists of a BPSK receiver and a BPSK transmitter, operating independently, but physically connected for low mass.

The transmitter and receiver are also available as standalone units. Our transmitter model is MST-765 and receiver is MSR-765.

The MSX-765 is easily integrated with L3 T&RF's MCU-110 (standalone integrated encryptor/decryptor) and has flight heritage on the COSMIC-1and GeoEYE-1 programs.

FEATURES

- L-/S-Band transceiver
- Compact, lightweight
- BPSK command receiver uplink data rate 64 kbps, capable to 2 Mbps
- BPSK telemetry transmitter downlink data rate 2 Mbps, capable to 10 Mbps
- Flight-proven
- High-reliability, radiation-hardened
- Standalone transmitter or receiver configurations
- Diplexer (optional)

Use of U.S. DoD visual information does not imply or constitute DoD endorsement.

MSX-765

L-/S-BAND T&C TRANSCEIVER

SPECIFICATIONS

L-/S-BAND TRANSCEIVER

Receive frequency	Fixed, 2000 to 2110 MHz range

CARRIER ACQUISITION

Threshold (with modulation)	-125 dBm

ACQUISITION

Time	0.5 second maximum
Noise figure	3.5 dB typical, 4 dB maximum
Input VSWR	1.5:1, 50 Ω
Acquisition and tracking range	±100 kHz

MODULATION

Type	BPSK
Data rate	4 or 64 kbps commandable rates standard, capable to 2 Mbps
Threshold (10-5 BER)	-108 dBm at 64 kbps, -120 dBm at 4 kbps

OUTPUT INTERFACE

Outputs	Carrier lock Rx loop stress Bit-lock signal strength (AGC) Converter voltages Temperature

TRANSMITTER/BASEBAND

Output frequency	Fixed, 1690 MHz, Alternate L-Band frequencies available
Frequency stability	External 10 MHz reference required Internal transmitter reference source optional

RF OUTPUT POWER

Output power	5 W minimum
Output VSWR	1.5:1, 50 Ω
Phase noise	2° RMS maximum

TELEMETRY CHANNEL

Commands (optional)	Primary power ON/OFF
Telemetry	Power ON/OFF command Converter voltages Temperature
Command type	+28 V latching relay

INPUT INTERFACE

Modulation rates	1.024 MHz: 128 kbps maximum, 1.7 MHz: 256 kbps maximum
Convolutional encoding	R = 1/2, K = 7 (CCSDS or JPL type)

INPUT INTERFACE

	RS-422

POWER REQUIREMENTS

Input voltage	+68 VDC to +72 VDC
Power consumption	Transmitter: 35 W maximum Receiver: 8 W maximum

GENERAL

Dimensions	7.22 in. L x 3.55 in. W x 3.65 in. H
Weight	6 lb. maximum

ENVIRONMENTAL

Temperature	-19 °C to +51 °C (acceptance) -24 °C to +56 °C (protoflight)
Vibration	19.0 Grms
Radiation	100 krad (chassis)

OPTIONS

Transceiver integrated with diplexer

L3 Telemetry & RF Products

9020 Balboa Avenue
San Diego, CA 92123
Tel: 858.694.7500
800.351.8483

1515 Grundy's Lane
Bristol, PA 19007
Tel: 267.545.7000

Email: Sales.TRF@L3T.com
L3T.com/TRF

Cleared by DoD/OSR for public release under 13-S-0401 on 12/05/2012. Data, including specifications, contained within this document are summary in nature and subject to change at any time without notice at L3's discretion. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

ML505 Rev F